



FLASH 80W90 GEAR OIL

Description

80W90 Gear Oil is a high-performance lubricant designed for automotive gear systems. With a viscosity of 80W90, it offers excellent protection against wear, corrosion, and oxidation. This gear oil ensures smooth operation, enhanced gear durability, and efficient power transmission in a variety of vehicles and applications.

Application

Apply 80W90 Gear Oil for superior lubrication in automotive gear systems. Ideal for manual transmissions, differentials, and gearboxes, it optimizes power transfer, reduces friction, and extends gear life. Regularly change and maintain the gear oil to ensure smooth operation, protect against wear, and enhance overall performance.

BENEFITS

- MAXIMUM PROTECTION
- MINIMISES INVENTORY
- LONGER DRAIN INTERVALS



Product Performance Claims

-API GL-5 LSD	-GM HN1561
-MIL-L-2105 B/C/D	-DIN 51517-3
-AIST 224	-MACK GO-J
-AGMA 250.04	-MT-1
-FORD M2C1006-A/B	-US STEEL 224

Typical Characteristics

Name	Method	Units	FLASH 80W90 GEAR OIL
Volumetric Mass At 15°C	DIN 51757 D	kg/m ³	902
Viscosity At 40°C	ASTM D445	mm ² /s	140
Viscosity, Kinematic 100°C	ASTM D445	mm ² /s	14.5
Viscosity Index	ASTM D2270	-	101
Flash Point	ASTM D92	°C	204
Pour Point	ASTM D97	°C	-36

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.