



# FLASH ATF DEXRON VI FULLY

## Description

Dexron VI is a fully synthetic automatic transmission fluid designed for modern vehicles. It offers superior oxidation resistance, wear protection, and consistent performance in automatic transmissions, ensuring smooth shifts and extended transmission life. Compliant with General Motors' specifications, it meets the highest industry standards.

## Application

Dexron VI ATF is suitable for a wide range of automatic transmissions, including those in GM vehicles, as well as many other domestic and import models. Its advanced formula ensures optimal performance, protection, and compatibility with modern transmission systems.

## BENEFITS

- SUPERIOR PROTECTION
- OPTIMUM GEAR SHIFTS
- DURABLE TRANSMISSION SYSTEM



## Product Performance Claims

- TOYOTA WS,T D-2, T-III,T-IV
- FORD MERCON@ LV
- ZF TE-ML 09X
- MERCEDES BENZ :09, 236.01
- JASO M315 TYPE 1A
- SUZUKI ATF 3314,3317
- LEXUS JWS 3309
- NISSAN@ MATIC FLUIDS
- HYUNDAI/KIA SP-II/III/IV

## Typical Characteristics

Name	Method	Units	FLASH ATF DEXRON VI FULLY
Density @ 15°C, Relative	ASTM D4052	g/ml	0.847
Viscosity, Kinematic 100 °C	ASTM D445	mm <sup>2</sup> /s	6.1
Pour Point	ASTM D97	°C	-54
Viscosity, Brookfield @ -40°C	ASTM D2983	mPa.s (cP)	10000
Viscosity ,Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	30.2
Viscosity Index	ASTM D2270	None	148
Flash Point , COC	ASTM D92	°C	206

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.