



## FLASH ATF SP III

### Description

ATF SP III, a Hyundai/Kia-specific automatic transmission fluid, boasts superior friction characteristics, oxidation stability, and wear protection. Tailored to meet the stringent requirements of Hyundai and Kia transmissions, it ensures optimal performance, smooth shifting, and extended durability in compatible vehicles.

### Application

ATF SP III is exclusively designed for Hyundai and Kia automatic transmissions. Its specialized formulation guarantees reliable lubrication, precise friction control, and enhanced wear protection. Used in the specified transmissions, it ensures optimal performance, longevity, and smooth operation in Hyundai and Kia vehicles.

### BENEFITS

- SUPERIOR PROTECTION
- OPTIMUM GEAR SHIFTS
- DURABLE TRANSMISSION SYSTEM



### Product Performance Claims

- MERCEDES BENZ 236.01;09;  
10 ATF 3403M-115
- PROTON SP-III
- PERODUA ATF D3-SP
- ISUZU G052 990 (09M),  
BESCO ATF-III AND ATF-III
- MITSUBISHI DIAQUEEN SP-II/  
SP-III
- NISSAN MATIC D,J
- DAIHATSU AMMIX ATF D3-SP
- HONDA ATF Z-1 (EXCEPT IN CVTs)
- MAZDA ATF M-III/M-V
- HYUNDAI/ KIA SP-III
- SUBARU/ SUZUKI ATF-HP

### Typical Characteristics

Name	Method	Units	FLASH ATF SP III
Sae Viscosity Grade	-	-	SP III
Density At 15°C	ASTM D4052	g/cm3	0,855
Flash Point	ASTM D92	°C	180
Pour Point	ASTM D97	°C	-45
Kinematic Viscosity At 40°C	ASTM D445	cSt	38
Viscosity At 100°C	ASTM D445	cSt	7.5
Viscosity Index	ASTM D2270	-	169

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.