



FLASH ENGINE OIL 0W-16 FULLY

Description

The 0W-16 oil is a low-viscosity, high-performance synthetic motor oil designed for optimal fuel efficiency and engine protection. Its advanced formula provides superior lubrication, reduces friction, and enhances overall engine performance. Ideal for modern vehicles, the 0W16 oil ensures smooth operation and extends engine life.

Application

0W-16 is specifically engineered for application in modern, fuel-efficient engines. Its ultra-low viscosity enhances cold-start performance, reduces friction, and improves fuel economy. Ideal for high-efficiency vehicles, it ensures smooth operation, minimizes wear, and maximizes engine longevity in a range of driving conditions.

BENEFITS

- WEAR PROTECTION
- ENGINE SLUDGE PROTECTION
- PISTON CLEANLINESS
- LOW TEMPERATURE PERFORMANCE



Product Performance Claims

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00
FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

Typical Characteristics

Name	Method	Units	FLASH 0W-16 FULLY
Viscosity Grade	SAE J300	-	0W-16
Kinematic Viscosity at 40 °C	ASTM D445	mm ² /s	36.4
Kinematic Viscosity at 100 °C	ASTM D445	mm ² /s	7.1
Density at 15°C	ASTM D1298	kg/m ³	841.6
Viscosity Index	ASTM D2270	-	158
Pour Point	ASTM D97	°C	-42
OC Flash Point	ASTM D92	°C	244

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.