

FLASH ENGINE OIL OW-30 FULLY

Description

The 0W-30 oil is a synthetic lubricant with a balanced viscosity, offering excellent engine protection across various temperatures. It ensures optimal fuel efficiency, minimizes friction, and enhances overall engine performance. Ideal for modern vehicles, the 0W30 oil provides superior wear protection and maintains engine cleanliness for prolonged engine life.

Application

The 0W-30 oil is tailored for use in a variety of modern engines, delivering superior performance in cold starts and extreme temperatures. Its synthetic formulation provides optimal lubrication, minimizes friction, and ensures engine longevity. Ideal for high-performance and demanding driving conditions, the 0W30 oil is suitable for a wide range of vehicles.

BENEFITS

- WEAR PROTECTION
- ENGINE SLUDGE PROTECTION
- PISTON CLEANLINESS
- LOW TEMPERATURE PERFORMANCE

FLESH FROM OIL ON 30 THE PROPERTY OF THE PR

Product Performance Claims

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

Typical Characteristics

Name	Method	Units	FLASH 0W-30 FULLY
Viscosity grade	SAE J300	-	0W-30
Density at 15°C	ASTM D1298	kg/m3	849.9
Kinematic Viscosity at 40 °C	ASTM D445	mm²/s	55.8
Kinematic Viscosity at 100°C	ASTM D445	mm²/s	10.1
Viscosity Index	ASTM D2270	-	171
Pour Point	ASTM D97	°C	-35
OC Flash Point	ASTM D92	°C	238

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.