



FLASH ENGINE OIL 10W-30 MINERAL

Description

10W-30 mineral oil is a conventional motor oil with a viscosity suitable for a variety of engines. Derived from refined crude oil, it provides essential engine lubrication, protecting against wear and ensuring proper functioning. Ideal for standard driving conditions, it balances viscosity for reliable year-round performance.

Application

10W-30 mineral oil is commonly used in older gasoline engines and light-duty vehicles, offering reliable lubrication in moderate climates. Its viscosity range ensures proper cold start protection and consistent high-temperature performance. Suitable for everyday driving, it provides cost-effective engine protection without the advanced features of synthetic counterparts.

BENEFITS

- WEAR PROTECTION
- ENGINE SLUDGE PROTECTION
- PISTON CLEANLINESS
- LOW TEMPERATURE PERFORMANCE



Product Performance Claims

- API SM/CI-4
- ACEA A3/B3-04,A3/B4-04
- MB 229.1
- VW 505.01/VW502.00VV

Typical Characteristics

Name	Method	Units	FLASH 10W-30 MINERAL
Viscosity Grade	SAE J300	-	10W-30
Kinematic Viscosity at 40 °C	ASTM D445	mm ² /s	72
Kinematic Viscosity at 100 °C	ASTM D445	mm ² /s	10.80
Density At 15°C	ASTM D1298	Kg/m ³	869
Viscosity Index	ASTM D2270	-	140
Pour Point	ASTM D97	°C	-36
OC Flash Point	ASTM D92	°C	230

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.