



## FLASH ENGINE OIL 10W-40 MINERAL

### Description

10W40 mineral oil is a traditional engine lubricant with a viscosity grade of 10W40. Composed of mineral base oils, it provides reliable engine protection by minimizing friction and wear. Ideal for older engines, it offers cost-effective lubrication and maintains performance in a range of operating conditions.

### Application

Use 10W40 mineral oil for dependable engine lubrication, particularly in older vehicles. Designed for a variety of driving conditions, it minimizes friction, reduces wear, and ensures proper engine protection. Regularly change the oil to maintain optimal performance and extend the life of the engine in diverse operating environments.

### BENEFITS

- WEAR PROTECTION
- ENGINE SLUDGE PROTECTION
- PISTON CLEANLINESS
- LOW TEMPERATURE PERFORMANCE



### Product Performance Claims

- API SM/CI-4
- ACEA A3/B3-04,A3/B4-04
- MB 229.1
- VW 505.01/VW502.00VV

### Typical Characteristics

Name	Method	Units	FLASH 10W-40 MINERAL
Viscosity grade	SAE J300	-	10W-40
Kinematic Viscosity at 40 °C	ASTM D445	mm <sup>2</sup> /s	93.1
Kinematic Viscosity at 100 °C	ASTM D445	mm <sup>2</sup> /s	14.1
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	866
Viscosity Index	ASTM D2270	-	155
Pour Point	ASTM D97	°C	-30
OC Flash Point	ASTM D92	°C	232

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.