



FLASH ENGINE OIL 5W-20 FULLY

Description

The 5W-20 oil is a high-quality synthetic lubricant engineered for optimal engine performance. With a balanced viscosity, it provides excellent protection in various temperatures, reducing friction and enhancing fuel efficiency. Ideal for modern vehicles, the 5W20 oil ensures smooth operation, longevity, and improved overall engine health.

Application

The 5W-20 oil is designed for versatile use in modern engines, excelling in cold starts and varying temperatures. Its balanced viscosity ensures efficient lubrication, reducing friction and improving fuel economy. Ideal for a broad range of vehicles, the 5W20 oil offers reliable protection, durability, and enhanced engine performance.

BENEFITS

- WEAR PROTECTION
- ENGINE SLUDGE PROTECTION
- PISTON CLEANLINESS
- LOW TEMPERATURE PERFORMANCE



Product Performance Claims

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00
FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6

Typical Characteristics

Name	Method	Units	FLASH 5W-20 FULLY
Viscosity grade	SAE J300	-	5W-20
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	44
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	8.2
Density at 15°C	ASTM D4052	kg/m ³	851
Viscosity Index	ASTM D2270	-	161
Pour Point	ASTM D97	°C	-33
OC Flash Point	NF EN ISO 2592*	°C	187

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.