



FLASH ENGINE OIL 5W-30 FULLY

Description

The 5W-30 fully synthetic oil is an advanced lubricant designed for superior engine protection. With a viscosity of 5 at low temperatures and 30 at high temperatures, it offers excellent fuel efficiency, wear resistance, and thermal stability. Ideal for modern engines, ensuring optimal performance and longevity.

Application

The 5W-30 oil is recommended for gasoline and diesel engines, 5W30 Fully Synthetic oil provides exceptional protection and performance. Its versatile application is suitable for various driving conditions, ensuring optimal lubrication, engine cleanliness, and fuel efficiency for modern engines.

BENEFITS

- WEAR PROTECTION
- ENGINE SLUDGE PROTECTION
- PISTON CLEANLINESS
- LOW TEMPERATURE PERFORMANCE

Product Performance Claims

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL_L_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00 FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6



Typical Characteristics

Name	Method	Units	FLASH 5W-30 FULLY
Viscosity grade	SAE J300	-	5W-30
Kinematic Viscosity at 40 °C	ASTM D445	mm ² /s	61
Kinematic Viscosity at 100 °C	ASTM D445	mm ² /s	11
Density at 15°C	ASTM D2198	kg/m ³	851,8
Viscosity Index	ASTM D2270	-	175
Pour Point	ASTM D97	°C	-45
OC Flash Point	ASTM D92	°C	226

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.