



## FLASH ENGINE OIL 5W-40 FULLY

### Description

5W40 Fully Synthetic oil is a high-performance lubricant formulated for optimal engine protection. With a viscosity of 5 at low temperatures and 40 at high temperatures, it provides excellent wear resistance, thermal stability, and fuel efficiency. Ideal for modern engines, ensuring superior performance in various driving conditions.

### Application

The 5W-40 oil is ideal for both gasoline and diesel engines, 5W40 Fully Synthetic oil offers superior protection and performance. Its versatile application makes it suitable for high-performance and demanding driving conditions, ensuring optimal lubrication, engine cleanliness, and extended engine life.

### BENEFITS

- WEAR PROTECTION
- ENGINE SLUDGE PROTECTION
- PISTON CLEANLINESS
- LOW TEMPERATURE PERFORMANCE

### Product Performance Claims

- API SP/SN/SN PLUS/ SM/SL/SJ/ILSAC GF-6A
- ACEA A3/B4-12, ACEA C3-10
- MIL\_L\_4615D & CID A-A-52039B, FORD WSS-M2C947-A, CHRYSLER MS6395-H, MB 229.1, VW 505.00  
FIAT 9.55535.D2
- MITSUBISHI, NISSAN, MAZDA, SUZUKI, TOYOTA, HONDA /ACURAHTO-6



### Typical Characteristics

Name	Method	Units	FLASH 5W-40 FULLY
Viscosity grade	SAE J300	-	5W-40
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	90
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	14.7
Density at 15°C	ASTM D1298	kg/m <sup>3</sup>	855
Viscosity Index	ASTM D2270	-	172
Pour Point	ASTM D97	°C	-39
OC Flash Point	ASTM D92	°C	230

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.