



FLASH ATF DEXRON III

Description

Dexron III is an automatic transmission fluid with enhanced friction durability and oxidation stability. It provides smooth shifting, protects against wear, and ensures optimal performance in automatic transmissions.

Application

Dexron III is designed for use in automatic transmissions, power steering systems, and hydraulic applications in vehicles. Its high-quality formulation ensures proper lubrication, friction control, and heat resistance, contributing to reliable and efficient operation in a variety of automotive systems.

BENEFITS

- SUPERIOR PROTECTION
- OPTIMUM GEAR SHIFTS
- DURABLE TRANSMISSION SYSTEM

Product Performance Claims

- GM DEXRON III, III F, III G
- GM TYPE A SUFFIX A
- MERCEDES BENZ MB 236.1, MB 236.9
- MAN 339-V2/339-Z2, 339 TYPE VI/ 339 TYPE Z1
- MB-APPROVAL 236.9
- VOLVO STD 1273.41 (97341)
- VOITH H55.6335XX
- FORD MERCON IV, FORD M2C-138CJ
- HOLDEN HN 2126
- MAZDA M III FLUID
- NISSAN ECVT



Typical Characteristics

Name	Method	Units	FLASH ATF DEXRON III
Colour	ASTM D1500	-	Red
Specific Gravity @ 15°C	ASTM D1122	Kg/dm ³	0.842
Kinematic Viscosity at 40 °C	ASTM D445	mm ² /s	31.3
Kinematic Viscosity at 100 °C	ASTM D445	mm ² /s	7.0
Dynamic Viscosity @ -40°C	mPa.s(cP)		20,000 max
Viscosity Index	ASTM D2270	-	196
Pour Point	ASTM D97	°C	-42
Flash Point	ASTM D92	°C	177 min

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

When used as directed and in accordance with the provided Material Safety Data Sheet (MSDS), this product is not anticipated to have negative health impacts. MSDS documents can be obtained through your sales contract office or online. Refrain from using the product for unintended purposes, and when disposing of used product, ensure environmentally responsible practices are followed.